

PRODUCT DESCRIPTION

A product that will assist users when sanding surfaces.

- * Highlights sanding marks on surface
- * Shows area not sanded
- * Will reduce print thru by enabling scratch marks from sanding to be more easily seen and then removed

PRODUCT INFORMATION

Colour	YMA180
Specific Gravity	0.87
Volume Solids	0.50%
Typical Shelf Life	2 yrs
VOC (As Supplied)	870 g/lt
Unit Size	1 Lt

DRYING/OVERCOATING INFORMATION

Drying

Overcoating Substrate Temperature

Overcoated By	5°C (41°F)		10°C (50°F)		23°C (73°F)		35°C (95°F)	
	Min	Max	Min	Max	Min	Max	Min	Max

Note: Remove all Sanding Guide Coat prior to application of subsequent coatings.

APPLICATION AND USE

Method	Wipe onto surface using a clean cloth/rag. For further advice read label instructions or Sanding Guide Leaflet or contact International's Free Helpline Service.
Hints	Other Remove all Sanding Guide Coat prior to application of subsequent coatings.
Some Important Points	Does not work on dark coloured surfaces.
Compatibility/Substrates	Light to medium coloured primers, undercoats and topcoats applied over any substrate.
Coverage	(Theoretical) - 50.0 m ² /lt
Application Methods	Cloth

TRANSPORTATION, STORAGE AND SAFETY INFORMATION

Storage	TRANSPORTATION: Sanding Guide Coat should be kept in securely closed containers during transport and storage. STORAGE: Exposure to air and extremes of temperature should be avoided. For the full shelf life of Sanding Guide Coat to be realised ensure that between use the container is firmly closed and the temperature is between 5°C/41°F and 35°C/95°F. Keep out of direct sunlight.
Safety	DISPOSAL: Do not discard tins or pour paint into water courses, use the facilities provided. It is best to allow paints to harden before disposal. GENERAL: Read the label safety section for Health and Safety Information, also available from our Technical Help Line. Always use gloves and goggles and keep skin protected with overalls.

IMPORTANT NOTES

The information given in this sheet is not intended to be exhaustive. Any person using the product without first making further written enquiries as to the suitability of the product for the intended purpose does so at their own risk and we can accept no responsibility for the performance of the product or for any loss or damage (other than death or personal injury resulting from negligence) arising out of such use. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.

Please refer to your local representative or visit <http://www.yachtpaint.com> for further information.

All trademarks mentioned in this publication are owned by, or licensed to, the AkzoNobel group of companies. © AkzoNobel 2014.